

CR-S002

COG

Design for mounts 6 bolt disc-hub to convert your bike into a fixed wheel and with special adapter to fixed on cassette hub to change to single speed / Very tight tolerances before undergoing heat treatment also with 6 stainless bolt. This is a cog for single speed disc hub and a cassette hub. Please do not remove any brake on your bike!!

- Material: cold forged Cr-Mo heat treated steel (ASM4140) and alloy 6061-T6 for the adapter.
- Color: N.E.N finished for cog red anodize for adapter.
- Use for disc hub 6hole and shimano cassette hub.
- Teeth: □16T, □17T, □18T, □19T, □20T, □21T, □22T, □23T


CR-S002

齒盤


專為碟刹花鼓與SHIMANO CASSETTE花鼓所設計，使用鉻鉬鋼材質所製成，熱處理加工，能將碟刹花鼓轉為單速花鼓，使用轉換片也能鎖固於CASSETTE花鼓，專為齒盤花鼓裝配於單速車所設計的齒片，請勿將任何刹車系統拆卸。

- 材質: 鉻鉬鋼冷鍛成型，熱處理加工，轉換片材質鋁6061-T6
- 表面: 無電解鍍防鏽處理 / 轉換片陽極色處理
- 規格: SHIMANO CASSETTE與碟刹花鼓專用
- 齒數規格: □16齒, □17齒, □18齒, □19齒, □20齒, □21齒, □22齒, □23齒

Single speed disc hub



1. For single disc hub you have to remove the cog with the alloy adapter because you only need the cog to fix on.
2. Remove the wheel set from your bike. Using the disc bolt to tighten the cog on the ISO standard 6 bolt mounting, for this cog there is no spacers for you to adjust the chain line.




3. Install your chain and wheel set to the bike and check every part is will tighten before you go ride.
4. As the cog is bolted (fixed) to the hub it can be driven by the chain forwards or backwards and becomes a fixed wheel. Check the gear is running smooth and all bolt is tighten and go ride.

Single speed disc hub




1. 當使用單速碟刹花鼓時請將兩側轉換片卸下。
2. 將後輪組卸下，使用碟盤鎖固螺絲將齒片鎖緊，請注意這項產品無法使用墊片調整正確的鏈條中心線。




3. 將後輪組裝配回車架上，並將鏈條一併組立回齒片上，再次確認後輪確實鎖固於車架上。
4. 當齒片組立於後輪上此系統將會轉變為單速車系統，請檢查鏈條轉動順暢並無任何干涉問題。


Cassette Hub



1. Remove your Cassette Sprocket off your bike by tool.
2. Install the single speed cog into your cassette hub, remember to put the spacers to adjust the cog on right chain line, we have 10mm, 5mm, 3mm spacers for you to chose.




3. When you have finished step 2 after that you can tighten the lock ring.
4. Install your chain and wheel set to the bike and check every part is will tighten before you go ride.
5. Check the gear is running smooth and all bolt is tighten and go ride.



Cassette Hub



1. 使用工具將飛輪卸下。
2. 將單速齒片裝入花鼓溝並使用口件的墊圈來調整齒片至正確的鏈條中心線。



3. 使用工具將迫緊環鎖上，並再次確認齒片已鎖緊。
4. 將後輪組配回車架上，並將鏈條一併組立回齒片上，再次確認後輪確實鎖固於車架上。
5. 檢查鏈條轉動順暢並無任何干涉問題。

