


CR-S001

COG

Design for cassette to convert your bike into a single speed hub cog is made by harden cold forged Cr-Mo steel (ASM4140) to make it super strong and long life use / Very tight tolerances before under going heat treatment from size 12t, 16t~23t to fix most of the rider requirement. This is a cog for single speed disc hub and a cassette hub.

- For cassette hub.
- Material: Cold forged Cr-Mo heat treated steel (ASM4140) N.E.N finished.
- With CAP (M-HUB) x 1pcs & Spacer (AR-HUB)
- 10mmx1pcs, 5mmx2pcs, 3mmx2pcs, 2mmx1pcs .
- Teeth: □12T, □16T, □17T, □18T, □19T, □20T, □21T, □22T, □23T



1. Remove your Cassette Sprocket off your bike by tool.
2. Install the single speed cog into your cassette hub, remember to put the spacers to adjust the cog on right chain line, we have 10mm, 5mm, 3mm spacers for you to choose.
3. When you have finished step 2 after that you can tighten the lock ring.
4. Install your chain and wheel set to the bike and check every part is will tighten before you go ride.
5. Check the gear is running smooth and all bolt is tighten and go ride.


www.fouriers-bike.com

CR-S001

齒盤

CASSETTE花鼓專用單速後齒片，使用鉻鉬鋼材質所製成，經過熱處理加工比市面上未熱處理的齒片，在使用壽命上有很大的優勢。

- CASSETTE專用
- 材質：鉻鉬鋼冷鍛成型，熱處理加工
- 表面：無電解鍍防鏽處理
- 一組包含(鎖固環與墊圈) 10mm1入, 5mm2入, 3mm2入, 2mm1入
- 齒數規格：□12齒, □16齒, □17齒, □18齒, □19齒, □20齒, □21齒, □22齒, □23齒



1. 使用工具將後飛輪卸下。
2. 將單數齒片裝入花鼓溝槽並使用零件的墊圈來調整齒片至正確的鏈條中心線。
3. 使用工具將鎖緊環鎖上，並再次確認齒片已鎖緊。
4. 將後輪組裝配回車架上，並將鏈條一併組立回齒片上，再次確認後輪確實鎖固於車架上。
5. 檢查鏈條轉動順暢並無任何干涉問題。

www.fouriers-bike.com